



INSTALLATION INSTRUCTIONS

DTD - Dusk-to-Dawn w/Twistlock Photocell



SAFETY PRECAUTION:

- Read instructions carefully before attempting to install fixture. Retain instructions for future reference.
- Disconnect power before installing or servicing. This fixture must be wired in accordance with the National Electrical Code and applicable local codes and ordinances.
- All wiring should be performed by a qualified electrician. This fixture is for outdoor use and should not be used in areas with limited ventilation or high ambient temperatures.

SPECIFICATIONS:

Model	Input Voltage	Input Current	Watts	Power Factor
DTD-95/CO/850-DIM-GY-U	100-277VAC	1.0A	80W	≥0.9
DTD-140/B5/850-DIM-GY-U	100-277VAC	1.0A	120W	≥0.9

INSTALLATION:

Surface Mount

1. Please see label on the fixture for specifications.
2. Use expansions bolts to secure the fixture on mounting surface. (Fig 1 & Fig 2)
3. Connect wires into terminal; white wire to “Neutral” terminal, black wire to “Live” terminal, green wire to “Ground” terminal; and fix them with wire connectors.

Surface Mount w/Arm

1. Connect wires; white to “Neutral”, black to “Line” and green to “Ground”.
2. Put end of the mounting arm tube into the U-slot, then fix the arm with two hex socket screws. Please make sure the arm will not rotate. (Fig 3)
3. Fix clamp to the arm and ensure the arm will not rotate. Install the fixture to the wall with four screws.

